## **TECHNICAL INFORMATION #13**



### **LEED and STAUF Adhesives**

STAUF USA, LLC is proud of its record as a leader in developing environmentally friendly products. STAUF is a founding member of the Association for the Control of Emission in Products for Flooring Installation (GEV), a European industry association whose goals are to promote the safety of consumers, trades, and the environment in the field of chemical construction materials.

Our products have received the GEV's highest certifications for meeting environmental standards, the coveted EMICODE EC1® Plus.

STAUF is also a member of the U.S. Green Building Council (USGBC), a 501(c)(3) non-profit composed of leaders from every sector of the building industry working to promote buildings and communities that are environmentally responsible, profitable, and healthy places to live and work. USGBC has developed the LEED® (Leadership in Energy and Environmental Design) Green Building Rating System. The LEED Rating System is the nationally accepted benchmark for designing, constructing, and operating high-performance green buildings.

With this document, STAUF declares that the products listed comply with Rule 1168 of California's South Coast Air Quality Management District's Volatile Organic Compounds (VOC) limits and the emission limits outlined in CDPH Standard Method v1.2. These are the mandatory requirements set by the USGBC LEED program for credit towards Low-Emitting materials (Interior Adhesives and Sealants applied on-site), as specified in the Green Building Rating System guideline v4. The LEED credit intends to reduce concentrations of chemical contaminants that can damage air quality, human health, productivity, and the environment.

These STAUF products can contribute to your qualification efforts for LEED certification under Indoor Air Quality Sections 3.1, 4.1, 4.2, and 4.3, as specified in the LEED 2009 for New Construction and Major Renovations. In addition, LEED credits intend to reduce the number of indoor air contaminants that are odorous, potentially irritating, and harmful to both installers and occupants.

A complete list of STAUF LEED qualifed products is on the following page.

Visit www.staufusa.com for more information, or call Technical Services at (901) 820-0007.

# **TECHNICAL INFORMATION #13**



## **LEED and STAUF Adhesives**

#### **Subfloor Prep**

- CCF-40 Concrete Crack Filler
- DJF-60 Dynamic Joint Filler
- ULC-500 LevelSeal

#### **Subfloor Primer**

- AQP-200 Eco-Prime
- EHS-265 Hydro-Seal

#### Subfloor Sealer

- ACS-210 True-Seal
- VPU-155"S" Urethane Sealer
- ERP-270 Perma-Seal®
- ERP-275 Rapid-Seal

#### **Wood Adhesive**

- PUM-950 Power-Mastic
- SMP-960 One-Step®
- SMP-920 Contractor Polymer
- PUM-955 Ultra-Nail®
- CBR-970 Renovator
- TGL-810 Tongue/Groove Glue
- PUK-455 Wide Plank Adhesive
- WFR-930 Solva-Mastic<sup>®</sup>
- AEM-852 Premium Acrylic-Ester

## **Resilient Flooring Adhesive**

- D-737 High-Tack
- LVP-777 Pro-Lux
- D-737ESD High-Tack
- MPB-821 Contractor's Multipurpose
- MPP-825 Premium Multipurpose
- BCS-827 Commercial Carpet
- BCF-828 Commercial Carpet Fast Set
- PSA-832 Pressure Sensitive
- CTS-837 VCT Clear Thin Spread
- CBA-843 Cove Base
- UVF-867 Vinyl Flooring
- R701 Xtreme-Link Duo
- R731 Poly-Link
- R741 Fxtreme-Link Mono

#### **Turf Adhesive**

R721 Synthetic Turf Adhesive