

## Approved Underlayments For Use With STAUF Adhesives

NAME OF UNDERLAYMENT	STAUF PRODUCTS									
	PUK-455	R701 / 741	D737	LVP-777	PIC-850 / 910	WFR-930	SMP-920	PUM-950	SMP-960	CBR-970
AcustiCork RC 1000	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Acusti-Tech Membrane by Sinitec, Inc., Canada										
Advantech OSB	◆	◆	◆	◆	◆	◆				
Cushion N Tred	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
DinoFlex Rubber Underlayment	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Diversified Floor Muffler										
Dura-Son Poly By Dura-Son	◆	◆	◆	◆	◆		◆	◆	◆	◆
Eco Ultimate Silencer by Foam Products	◆	◆			◆					
Ecore QT350x and QT 400x (x=any thickness)	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Floor Muffler										
Floor Muffler LVT			◆	◆						
GenieMat RST	◆	◆	◆	◆	◆		◆	◆	◆	◆
Insulayment by Midwest Padding, LLC	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Konecto MSS-KD-200R										
New Dura-Son w/ Pe										
NRT QD Granulated and NRT QD Max	◆	◆	◆	◆	◆		◆	◆	◆	◆
NRT QD Max HB	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
NRT Quiet Down RC Acoustic Underlay	◆	◆	◆	◆	◆		◆	◆	◆	◆
PROFLEX 40CISM, 70SSC, 90MSC	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
PROFLEX by Primary Acoustics	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
ProtectoWrap Whisper Mat-HW	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Quiet-Core by Tarkett	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Quietdown Tile by National Rubber Technology	◆	◆	◆	◆	◆		◆	◆	◆	◆
Quit Sound II	◆	◆	◆	◆	◆		◆	◆	◆	◆
RB Rubber Athletic 'Rolled Rubber Flooring'	◆	◆	◆	◆	◆		◆	◆	◆	◆
RB Rubber, 2mm & 6mm	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Sound Deadener										
Sound Solution by Healthier Choice	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Sureflexx by US Rubber	◆	◆	◆	◆	◆		◆	◆	◆	◆
The Silencer by Foam Products Corp.	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
VERDEX by Smirnoff Building Systems	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Vinyl Trends BLK TXT LVT / UHD / Eternity LVT SK & TW			◆	◆						
Vinyl Trends WHT / Vinyl Trends WHT LVT	◆	◆	◆	◆	◆		◆	◆	◆	◆
Volara Foam										
Warmboard R and S	◆							◆		
XLPE 4# Solid Black MD										
XLPE 2# Sound Barrier Select										

### Important Notes:

- WFR-930 will typically dry more slowly and may create short term cupping due to non-absorbing properties of the various underlayments.
- D737 & LVP-777 should only be used for installation of underlayment if resilient flooring will be installed on top of the underlayment, not for subsequent wood flooring installation
- It is the installer's responsibility to test for compatibility of all underlayments with the adhesive being used due to manufacturers changing raw materials from time to time.

Visit [www.staufusa.com](http://www.staufusa.com) for more information, or call Technical Services at (901) 820-0007.